



HERMÓD

The vest LV 09 is simple bullet-proof vest ensuring comfortable wearing without movement restriction. The vest provides front, back and shoulder ballistic protection and front and back hard ballistic panels. Fastening of the vest is in the shoulder part and hips parts of the body.


The vest is standardly produced in these colours. It is possible to produce the vest in other colours. For more information please contact us.



MultiCam



Black



Czech Army
woodland pattern 95

Specifications:

- Soft ballistic panels at the front, back and on shoulders parts of the vest.
- Front and back pockets for hard ballistic panels.
- Front and back hard ballistic panels are inserted into the pockets in the outside of the vest.

- Size adjustment in hips and shoulder parts.
- Fastening of the vest in shoulder part is from back to front direction.

Material:



type	composition	dTex	weight [g/m ²]
Cordura 750	100% Cordura	770	260.0
Cordura 1000	100% Cordura	1100	337.0
Polyester	100% PES	167	300.0

Ballistic protection:

- level of ballistic protection: III.A according to the NIJ 0101.04
- levels of ballistic protection according to the soft ballistic panels ARMAX soft ballistic panels
- higher ballistic protection by hard ballistic panels

Options:

- Size: XS, S, M, L, XL, XXL
- Carrying bag

Level	Calibre	Weapon	Bullet weight	Bullet Velocity ($V_{2.25}$) \pm 9.14 m/s	Distance	Max. depth (mm)
I	.22LR	LRN, Remington	2.6 g (40 grain)	329	5 m	44
	.380 ACP	FMJ RN, Remington R380AP	6.2 g (95 grain)	322	5 m	44
IIA	9mm	FMJ RN, Remington R9MM2	8.0 g (124 grain)	341	5 m	44
	40 S&W	FMJ, Winchester B40TC180	11.7 g (180 grain)	322	5 m	44
II	9mm	FMJ N, Remington R9MM2	8.0 g (124 grain)	367	5 m	44
	.357 Mag	JSP, Remington R335M3	10.2 g (158 grain)	436	5 m	44
IIIA	9mm	FMJ RN, Remington R9MM2	8.0 g (124 grain)	436	5 m	44
	.44 Mag	SJHP Remington R44MG3	15.6 g (240 grain)	436	5 m	44



ČSN 395360 ZKOUŠKY
ODOLNOSTI OCHRANNÝCH
PROSTŘEDKŮ
AŽ DO ÚROVNĚ TBO3



UK PSDB BODY ARMOUR
STANDARDS
AŽ DO ÚROVNĚ HG2



NJ STANDARD - 0101.04
AŽ DO ÚROVNĚ IIIA



AVAILABLE BALLISTIC
INSERT